



ITL

INTRODUCING
18V

**A VERSATILE TRACTOR
THAT PROVES TO BE BETTER
THAN A POWER TILLER!**



**HIGHER PRODUCTIVITY
THAN POWER TILLER**



**EASY TO OPERATE
THAN POWER TILLER**



**HIGHER STABILITY
OFFERING SAFETY
THAN POWER TILLER**



**HIGHER SPEED
THAN POWER TILLER**

SPECIFICATIONS

FEATURES	ITL 18V
ENGINE 	
HP Category	18
No of Cylinder	1
Aspiration	Natural
Cubic Capacity	863.5 cc
Rated RPM	2300 ± 75
Air Cleaner	Dry type
Max Torque (Nm)	54@1200±200 RPM
Exhaust	Downdraft
TRANSMISSION 	
Drive	2WD
Gearbox	Sliding Mesh
Transmission	6F + 2R
SPEED (FORWARD) 	
Minimum Speed (Km/hr)	2.01
Maximum Speed (Km/hr)	25.19
BRAKES 	
Brakes	Oil Immersed
Type of Actuation	Mechanical
Parking Brake	Independent Parking Brakes
PTO 	
PTO (rpm)	540 & 540E
PTO (Actuation)	Mechanical
STEERING 	
Steering	Mechanical
ELECTRICALS 	
Battery	12V, 65 Ah
Alternator	12V, 36 H

*Data and specifications are subject to change without any advance notice due to continuous product improvement and development. All dimensions are with standard tires.

DEALER STAMP



FEATURES	ITL 18V
HYDRAULICS 	
3 Point Linkage	CAT 1
Stay Bars	Anchor Chain
Auxiliary Hydraulic Circuit	1TA
Lift Capacity (Kg)	700
Lift Rods	Standard
CAPACITY (LITRES ± 5%) 	
Fuel Tank	28 L
TYRE 	
Front	5.25 X 14
Rear	8 X 18
OVERALL WEIGHT & DIMENSIONS 	
Weight (Kg)	1160
Wheel Base (mm)	1485
Total Lenght (mm)	2745
Total Width (mm)	1165
Height (mm) Up to Muffler	1780
Min. Ground Clearance	220
Front Track (mm)	970
Rear Track (mm)	935
OTHERS 	
Front Toe Hook	Yes, Available



INTERNATIONAL TRACTORS LIMITED

International Business Office: Teri School of Advanced Studies, Plot No.10, Institutional Area, Vasant Kunj, New Delhi-110070 (India)
Phone: +91 11 66 45 5200 | Work: Jalandhar Road, Hoshiarpur - 146022, Punjab (India) | Phone: +91-01882-522220/ 522221
Fax:+91- 01882-522222 | Email: info@solisworld.com | URL: www.solistractors.com